

## LBB

### load bearing basket



## WBB

### wide body basket



	Body Width (in.)	Part No.	Rated Capacity* (lbs.) Vertical Basket	Eye Length (in.)	Minimum Sling Length (in.)
One Ply Eye	6	LBB1906	5,000	6	50
	8	LBB1908	5,000	8	50
	10	LBB1910	5,000	10	54
	12	LLB1912	5,000	12	56
	16	LBB1916	10,000	14	56
	20	LLB1920	10,000	16	68
	24	LBB1924	10,000	20	72
Two Ply Eye	6	LBB2906	10,000	10	50
	8	LBB2908	10,000	10	50
	10	LBB2910	10,000	12	54
	12	LBB2912	10,000	12	56
	16	LBB2916	18,000	12	56
	20	LBB2920	18,000	18	68
	24	LBB2924	18,000	18	72
	30	LBB2930	18,000		
	36	LBB2936	18,000		
	48	LBB2948	18,000		

## BOAT HULL SLINGS



Web Piles	Hull Saver Code	Width (in.)	1 Rated Capacity* (lbs.)	Optional Pull Pin Shackles			
				Shackle Code	W (in.)	L (in.)	Weight Each (lbs.)
Two Ply	HS2804	4	23,000	PPS-4	4	3.75	3.2
	HS2806	6	32,600	PPS-6	6	4.75	6.8
	HS2808	8	38,400	PPS-6HD	6	4.75	9.8
	HS2810	10	44,800	PPS-6HD	6	4.75	9.8
	HS2812	12	48,000/53,800 <sup>2</sup>	PPS-6HD <sup>2</sup>	6	4.75	9.8



Pull Pin Shackles (Optional)

- Notes: 1. Capacity in lbs. is the rating of one sling in a vertical basket hitch.  
2. Derate sling to 48,000 when used with 6" HD Shackle (PPS-6HD)