

Different Chain Configurations



SG



SOS



SOG



SOF



SOBK



SGG



SSS



SSG



ASOS



SOLK



DOS



DOG



DOF



DOBK



DOO



BS



ADOS



DOLK




TOS



TOG



TOF



TPBK



ATOS



QOS



QOG



QOF



QOBK



ENDLESS



AQOS



BD



TYPE "A"



TYPE "B"

GR80 Alloy Chain Slings

WORKING LOAD LIMITS IN POUNDS – DESIGN FACTOR 4

GR80 ALLOY CHAIN SIZE		Single Leg	Double Leg				Triple and Quad Leg		
		90 DEGREES	60 DEGREES	45 DEGREES	30 DEGREES	90 – 60 DEGREES	90 – 45 DEGREES	90 – 30 DEGREES	
(mm)	(in)								
6	7/32	2100	3600	3000	2100	5450	4450	3150	
7	1/4 9/32	3500	6100	4900	3500	9100	7400	5200	
8	5/16	4500	7800	6350	4500	11700	9550	6750	
10	3/8	7100	12300	10000	7100	18400	15100	10600	
13	1/2	12000	20800	17000	12000	31200	25500	18000	
16	5/8	18100	31300	25600	18100	47000	38400	27100	
20	3/4	25500	44100	36000	25500	66200	54000	38200	
22	7/8	34200	59200	48400	34200	88900	72500	51300	
26	1	47700	82600	67450	47700	123900	101200	71550	
32	1-1/4	72300	125200	102200	72300	187800	153400	108400	

GR100 Alloy Chain Slings

WORKING LOAD LIMITS IN POUNDS – DESIGN FACTOR 4

GR100 ALLOY CHAIN SIZE		Single Leg	Double Leg				Triple and Quad Leg		
		90 DEGREES	60 DEGREES	45 DEGREES	30 DEGREES	90 – 60 DEGREES	90 – 45 DEGREES	90 – 30 DEGREES	
(mm)	(in)								
6	7/32	2,700	4,700	3,800	2,700	7,000	5,700	4,000	
7	1/4 9/32	4,300	7,400	6,100	4,300	11,200	9,100	6,400	
8	5/16	5,700	9,900	8,100	5,700	14,800	12,100	8,500	
10	3/8	8,800	15,200	12,400	8,800	22,900	18,700	13,200	
13	1/2	15,000	26,000	21,200	15,000	39,000	31,800	22,500	
16	5/8	22,600	39,100	32,000	22,600	58,700	47,900	33,900	
20	3/4	35,300	61,100	49,900	35,300	91,700	74,900	53,000	
22	7/8	42,700	74,000	60,400	42,700	110,900	90,600	64,000	
26	1	59,700	103,400	84,400	59,700	155,100	126,600	89,500	
32	1-1/4	90,400	156,600	127,800	90,400	234,900	191,800	135,600	

GR120 Alloy Chain Slings

WORKING LOAD LIMITS IN POUNDS – DESIGN FACTOR 4

GR120 ALLOY CHAIN SIZE		Single Leg	Double Leg				Triple and Quad Leg		
		90 DEGREES	60 DEGREES	45 DEGREES	30 DEGREES	90 – 60 DEGREES	90 – 45 DEGREES	90 – 30 DEGREES	
N1720	9/32	5,200	9,000	7,400	5,200	13,500	11,000	7,800	
N1820	5/16	6,600	11,400	9,300	6,600	17,100	14,000	9,900	
NI1020	3/8	10,600	18,400	15,000	10,600	27,500	22,500	15,900	
NI1320	1/2	17,900	31,000	25,300	17,900	46,500	38,000	26,900	
NI1620	5/8	27,500	47,000	38,500	27,500	71,500	58,000	41,500	